


SPECIFICATIONS

Size	Metric	British
Max. Working Height(Indoor)	15.70m	51ft 6in
Max. Platform Height(Indoor)	13.70m	44ft 11in
Max. Working Height(Outdoor)	11.00m	36ft 1in
Max. Platform Height(Outdoor)	9.00m	29ft 6in
Overall Length ©	2.84m	9ft 4in
Overall Width ①	1.25m	4ft 1in
Overall Height(Rails Up)	2.62m	8ft 7in
Overall Height(Rails Down)	2.09m	6ft 10in
Platform Size(Length×Width)	2.64m×1.12m	8ft 8in×3ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase (2.22m	7ft 3in
Turning Radius(Inside/Outside)	0m/2.65m	0/8ft 8in
Tyres	φ381×127mm	φ381×127mm

250kg	551lb
113kg	249lb
2/0	2/0
25%	25%
5.0km/h	3.10mph
0.8km/h	0.50mph
X-1.5°/Y-3°	X-1.5°/Y-3°
62/62sec	62/62sec
	113kg 2/0 25% 5.0km/h 0.8km/h X-1.5°/Y-3°

Weight			
Overall Weight	3580kg	7892lb	

Power		
Battery	24V/240Ah	24V/240Ah
Charger	24V/30A	24V/30A
Driving Motor	2×15VAC/0.87kW	2×15VAC/0.87kW
Upper Lifting Motor	24VDC/1.8kw	24VDC/1.8kw
Lower Lifting Motor	24VDC/3.0kW	24VDC/3.0kW







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- · Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











